



KN7P Printhead

KN16P The nozzle uses wear-resistant and durable gem material, which makes the dot of the jet more round and can be used for a long time.

KN32P The printhead can be rotated to achieve to print different characters and fonts.

Ink System

The design of stable and durable internal pump can make the printer work without air source.

White ink machine has automatic stirring system to prevent the pigment ink precipitation.



Main Hardware

High integration of the industrial level of the new motherboard works fast and stable, What it does it better to deal with the extremely harsh environment



KN DOD Series

DOD LARGE CHARACTER INKJET PRINTER

KN DOD series large character inkjet printer adopts high reliable Drop-On-Demand Inkjet solenoid valve technology.

Reliable, strong and durable performance can meet the needs of various industrial coding.

The printer can work normally in a variety of harsh environment, such as dust, humidity and vibrations.

The high precision technology makes reliable performance and minimal maintenance.

External Interface

With grade of IP68, the interface not only supports RS232 network interface, but also the count output, information control and other functions



TECHNICAL SPECIFICATIONS PRINTER DOD

Printing Parameters

Print Head Duct	3m/6m
Nozzle Specifications	80u, 120u, 150u
Printing Height	7dots: 5-28mm 16dots: 5-64mm 32dots: 5-128mm
Printing Distance	3-30mm
Printing Lines	1-4lines
Printing Speed	63m/min
Counter	More than 20 independent counters
Ink Color	Black, White, Blue, Red Green, Yellow, Invisible
Ink Type	MEK based, water based, N-propanol based, ethanol based, ethyl acetate based, acetone based
Font	Sx6L 7x6L 7x10L 9x8L 9x11L 11x11L 12x12L 16x16L 24x24L 32x32L 11x11B 12x13B 16x16B 24x24B 32x32B
Printing Material	Carton, Plastic, Metal, Sheet Material, Pipe, Stone, Glass, Electronic components, Industrial chemical packaging, Paint surface and other permeable and non-permeable surfaces
Print Content	Text, Time, Date(Julian Year), Logo, Shift, SN, Dynamic Barcode/QR Code, Dynamic Serial Data, Dynamic Da1abase(Additional content can be added as required)

490mm

Front view

Side view



296mm

296mm



Machine Parameters

Operating System	Embedded Linux security operating system
Display Screen	7 inch color display, industrial touch screen
Communication Interface	Network interface, USB, RS232
Protection Level	IP65
Power Parameters	Input 100-240V AC
Rated power	ISOW
Memory	256M
Machine Material	304 stainless steel
Machine Specifications	296mmx296mmx490mm(Lengthxwidthxheight)
Working Environment	Temperature 0-45°C/ Humidity 30-70%Rh
Related Certification	CE, RoHS FCC
Net Weight	16kg
Main Hardware	American TI AM3358 industrial grade CPU, American Xilinx Spartan-6 industrial grade FPGA
External Interface	Optical eye, Encoder, Signal light alarm output, Serial number control and transport, External printing information selection and flipped
Support Language	Support more than 40 national languages (Chinese, English, Arabic, Danish, German, Russian, French, Finnish, Korean, Japanese, Spanish, Italian, etc.)

Applications

- Wood
- Stone
- Tires
- Textile
- Bags
- Pipelines
- Painted surface



KODYKA
KN DOD Series



Printers for marking and industrial coding.

www.kodyka.com

📍 Avenida de Mendavia 11, Pabellón 16
26009 Logroño
La Rioja
España
☎ Telf: + 34 638 868 342
✉ info@kodyka.com